TECHNICAL DATA

INDUSTRIAL GROUND SOURCE HEAT PUMPS **IGLU Aleut Max**



TABLE OF CONTENTS

The sequence of IGLU TECH products configuration 3

Technical data of IGLU Aleut Max 24 – 90 kW fixed capacity brine/water heat pumps 4

Annex to the technical characteristics according to European Commission Regulation No 813/2013 5

Technical data of IGLU Aleut Max 24 fixed capacity heat pump 5

Technical data of IGLU Aleut Max 36 fixed capacity heat pump 6

Technical data of IGLU Aleut Max 45 fixed capacity heat pump 7

Technical data of IGLU Aleut Max 70 fixed capacity heat pump 8

Technical data of IGLU Aleut Max 90 fixed capacity heat pump 9

The sequence of IGLU TECH products configuration

X1 – IGLU Aleut/IGLU Aleut WT/IGLU Aleut I/IGLU Aleut WTI – AL;
X1 – IGLU ALEUT WTI (600x675X1800) – AS;
X1 – IGLU Inuit /IGLU Inuit WT – IN;
X1 – IGLU Aleut Max – MA;
X1 – IGLU Inuit Mono/IGLU Inuit Mono WT – MB;
X2 – Capacity of pump – 5/7/9... kW;
X3 – Kind of compressor (I – inverter/F – fixed speed);
X4 – Water tank – (W);
X5 – Active cooling – (A);
X6 – Passive cooling – (P);
X7 – Construction – Split (S);
X8 – Unit location – Inside/Outside, (I/O);
X9 – Energy supply:
Sr – single phase 1P 230 V;
Tr – triple phase 3P 400V;
Sn – single phase to north 2P 230 V;
Tn – triple phase to north 3P 230 V;
X10 – Agent (R 410A – a; R 407C – b; R32 – c; R 290 – d);
N – not applicable;

Technical data of IGLU Aleut Max 24 – 90 kW fixed capacity brine/water heat pumps

	Units	24 kW	36 kW	45 kW	70 kW	90 kW
Brine/water used						
Thermal power (B0/W35)[1)]	kW	24,85	35,5	43,98	71,08	87,3
Thermal power (B0/W45)[1)]	kW	23,59	33,7	42,65	66,15	82,5
COP (B0/W35)[1)]	-	4,54	4,65	4,45	4,58	4,53
COP (B0/W45)[1)]	-	3,37	3,74	3,59	3,52	3,48
SCOP (B0/W35)	-	5,71	5,76	5,77	5,75	5,66
SCOP (B0/W45)	-	4,14	4,22	4,30	4,42	4,22
Refrigeration capacity (B24/W10) [2]	kW	26,0	40,1	49,4	80,8	108,0
Brine circuit						
Rated flow (DT = 3K)[3)]	m³/h	8	9	12	17	23
Permissible external pressure drop[3)]	kPa	23	16	16	16	12
Maximum pressure	bar	4				
Volume (internal)	l	7			22	
Operating temperature	°C	from -10 to +20				
Connection (Cu)	mm	28		35	50	
Compressor						
Type		Spiral “Scroll”				
Mass of refrigerant R 410A[4)]	kg	-	-	3,85	8,25	9,5
Mass of refrigerant R 407C[4)]		2,5	3,45	-	-	-
Maximum pressure	bar	45			48	
Rated flow (DT = 7K)	m³/h	4	6	6,4	10	13
Min. flow temperature	°C	15				
Max. flow temperature	°C	60				
Max. permissible operating pressure	bar	4,0				
Connection (Cu)	mm/in	28 mm		35 mm	50 mm	2 ’’ (in)
Power network connection values						
Electrical connections		3/N/PE 400V/ 50Hz				
External circuit breaker;	A	20	25	32	50	63
RLA – rated load amps	A	15,9	21,6	27,6	44	57
Compressor rated power (B0/W35)	kW	5,2	7,6	10,1	14,65	19,25
Type of protection	IP	IP20				
General information						
Permissible ambient temperatures	°C	from +10 to +35				
Sound power level[5)]	dBA	55	56	56	57	64
Dimensions (width x depth x height)	mm	910 x 800 x 1400			910 x 1500 x 1400	
Weight (without packaging)	kg	150	170	220	475	520

1) With internal pump according to EN 14511
2) On models with an active cooling module
3) With ethylene glycol
4) Greenhouse potential, GWP100 = 1774
5) According to EN 3743-1

Annex No 1

Annex to the technical characteristics according to European Commission Regulation No 813/2013

Technical data of IGLU Aleut Max 24 fixed capacity heat pump

Model	IGLU Aleut Max 24
Air-to-water heat pump	No
Water-to-water heat pump	No
Ground-to-water heat pump	Yes
Low temperature heat pump	No
Equipped with supplementary heater	No
Supplementary heater is used	No

Parameters applied using average temperature are declared. Parameters are declared under average climatic conditions.

Parameter	Conventional representation	Value	Measurement unit
Rated thermal power	P_{rated}	24,85	kW
Declared part load heating capacity at 20 °C indoor temperature and outdoor temperature T_j			
T_j = – 7 °C	P_{dh}	24,07	kW
T_j = + 2 °C	P_{dh}	24,64	kW
T_j = + 7 °C	P_{dh}	25,18	kW
T_j = + 12 °C	P_{dh}	25,85	kW
T_j= (T_{iv})- bivalent temperature mode	P_{dh}	-	kW
T_j = operating limit temperature	P_{dh}	-	kW
Air-to-water heat pump: **T_j** = -15°C (where TOL <-20°C)	P_{dh}	-	kW
Bivalent temperature	T_{biv}	-	°C
Power in cyclic heating mode	P_{cych}	-	kW
Decreased efficiency in cyclic mode	C_{dh}	0,99	—
Power consumption in modes other than active mode			
Off mode	P_{OFF}	0,009	kW
Thermostat-off mode	P_{TO}	0,009	kW
Standby mode	P_{SB}	0,064	kW
Crankcase heater mode	P_{CK}	-	kW
Other parameters			
Capacity control	fixed		
Sound power level, indoors/outdoors	L_{WA}	55/0	dB
Emissions of nitrogen oxides	NO_x	-	mg/kWh

Parameter	Conventional representation	Value	Measurement unit
Seasonal energy efficiency for space heating	η_s	151	%
Declared efficiency coefficient or ratio of primary energy to radiant heat output at room temperature 20 °C and outdoor temperature T_j			
T_j = – 7 °C	COP_d or PER_d	4,56	–
T_j = + 2 °C	COP_d or PER_d	4,65	–
T_j = + 7 °C	COP_d or PER_d	4,79	–
T_j = + 12 °C	COP_d or PER_d	4,98	–
T_j= (T_{biv})- bivalent temperature mode	COP_d or PER_d	-	–
T_j = operating limit temperature	COP_d or PER_d	-	°C
Air-to-water heat pump: **T_j** = -15°C (where TOL <-20°C)	COP_d arba PER_d	-	
Air-to-water heat pump: operating limit temperature	TOL	-	°C
Cyclical efficiency	COP_{cyc} or PER_{cyc}	-	– or %
Heating water limit operating temperature	WTOL	60	°C
Supplementary heater			
Rated thermal power	P_{sup}	-	kW
Type of energy input	Electricity		
Air-to-water heat pump: rated air flow rate, outdoor	—		m^3/h
Ground-to-water heat pump: water flow, outdoor heat exchanger		8	m^3/h
Contact details	IGLU TECH UAB	Ukmerges st. 364-6, Vilnius, Lithuania	

Technical data of IGLU Aleut Max 36 fixed capacity heat pump

Model	IGLU Aleut Max 36
Air-to-water heat pump	No
Water-to-water heat pump	No
Ground-to-water heat pump	Yes
Low temperature heat pump	No
Equipped with supplementary heater	No
Supplementary heater is used	No

Parameters applied using average temperature are declared. Parameters are declared under average climatic conditions.

Parameter	Conventional representation	Value	Measurement unit
Rated thermal power	P_{rated}	35,5	kW
Declared part load heating capacity at 20 °C indoor temperature and outdoor temperature T_j			
T_j = – 7 °C	P_{dh}	35,01	kW
T_j = + 2 °C	P_{dh}	35,33	kW
T_j = + 7 °C	P_{dh}	35,54	kW
T_j = + 12 °C	P_{dh}	35,67	kW
T_j= (T_{biv})- bivalent temperature mode	P_{dh}	-	kW
T_j = operating limit temperature	P_{dh}	-	kW
Air-to-water heat pump: **T_j** = -15°C (where TOL <-20°C)	P_{dh}	-	kW
Bivalent temperature	T_{biv}	-	°C
Power in cyclic heating mode	P_{cych}	-	kW
Decreased efficiency in cyclic mode	C_{dh}	0,99	—
Power consumption in modes other than active mode			
Off mode	P_{OFF}	0,009	kW
Thermostat-off mode	P_{TO}	0,009	kW
Standby mode	P_{SB}	0,064	kW
Crankcase heater mode	P_{CK}	-	kW
Other parameters			
Capacity control	fixed		
Sound power level, indoors/outdoors	L_{WA}	56/0	dB
Emissions of nitrogen oxides	NO_x	-	mg/kWh

Parameter	Conventional representation	Value	Measurement unit
Seasonal energy efficiency for space heating	η_s	154	%
Declared efficiency coefficient or ratio of primary energy to radiant heat output at room temperature 20 °C and outdoor temperature T_j			
T_j = – 7 °C	COP_d arba PER_d	4,50	–
T_j = + 2 °C	COP_d arba PER_d	4,61	–
T_j = + 7 °C	COP_d arba PER_d	4,76	–
T_j = + 12 °C	COP_d arba PER_d	4,84	–
T_j= (T_{biv})- bivalent temperature mode	COP_d arba PER_d	-	–
T_j = operating limit temperature	COP_d arba PER_d	-	°C
Air-to-water heat pump: **T_j** = -15°C (where TOL <-20°C)	COP_d arba PER_d	-	
Air-to-water heat pump: operating limit temperature	TOL	-	°C
Cyclical efficiency	COP_{cyc} or PER_{cyc}	-	– or %
Heating water limit operating temperature	WTOL	60	°C
Supplementary heater			
Rated thermal power	P_{sup}	-	kW
Type of energy input	Electricity		
Air-to-water heat pump: rated air flow rate, outdoor	—		m^3/h
Ground-to-water heat pump: water flow, outdoor heat exchanger		9	m^3/h

Contact details	IGLU TECH UAB	Ukmerges st. 364-6, Vilnius, Lithuania	

Technical data of IGLU Aleut Max 45 fixed capacity heat pump

Model	IGLU Aleut Max 45
Air-to-water heat pump	No
Water-to-water heat pump	No
Ground-to-water heat pump	Yes
Low temperature heat pump	No
Equipped with supplementary heater	No
Supplementary heater is used	No

Parameters applied using average temperature are declared. Parameters are declared under average climatic conditions.

Parameter	Conventional representation	Value	Measurement unit
Rated thermal power	P_{rated}	43,98	kW
Declared part load heating capacity at 20 °C indoor temperature and outdoor temperature T_j			
T_j = – 7 °C	P_{dh}	44,37	kW
T_j = + 2 °C	P_{dh}	44,78	kW
T_j = + 7 °C	P_{dh}	44,96	kW
T_j = + 12 °C	P_{dh}	45,37	kW
T_j= (T_{biv})- bivalent temperature mode	P_{dh}	-	kW
T_j = operating limit temperature	P_{dh}	-	kW
Air-to-water heat pump: **T_j** = -15°C (where TOL <-20°C)	P_{dh}	-	kW
Bivalent temperature	T_{biv}	-	°C
Power in cyclic heating mode	P_{cych}	-	kW
Decreased efficiency in cyclic mode	C_{dh}	0,99	—
Power consumption in modes other than active mode			
Off mode	P_{OFF}	0,009	kW
Thermostat-off mode	P_{TO}	0,009	kW
Standby mode	P_{SB}	0,064	kW
Crankcase heater mode	P_{CK}	-	kW
Other parameters			
Capacity control	fixed		
Sound power level, indoors/outdoors	L_{WA}	56/0	dB
Emissions of nitrogen oxides	NO_x	-	mg/kWh
Contact details	IGLU TECH UAB		Ukmerges st. 364-6, Vilnius, Lithuania

Parameter	Conventional representation	Value	Measurement unit
Seasonal energy efficiency for space heating	η_s	142	%
Declared efficiency coefficient or ratio of primary energy to radiant heat output at room temperature 20 °C and outdoor temperature T_j			
T_j = – 7 °C	COP_d arba PER_d	4,61	–
T_j = + 2 °C	COP_d arba PER_d	4,72	–
T_j = + 7 °C	COP_d arba PER_d	4,88	–
T_j = + 12 °C	COP_d arba PER_d	4,97	–
T_j= (T_{biv})- bivalent temperature mode	COP_d arba PER_d	-	–
T_j = operating limit temperature	COP_d arba PER_d	-	°C
Air-to-water heat pump: **T_j** = -15°C (where TOL <-20°C)	COP_d arba PER_d	-	
Air-to-water heat pump: operating limit temperature	TOL	-	°C
Cyclical efficiency	COP_{cyc} or PER_{cyc}	-	– or %
Heating water limit operating temperature	WTOL	60	°C
Supplementary heater			
Rated thermal power	P_{sup}	-	kW
Type of energy input	Electricity		
Air-to-water heat pump: rated air flow rate, outdoor	—		m^3/h
Ground-to-water heat pump: water flow, outdoor heat exchanger		12	m^3/h

Technical data of IGLU Aleut Max 70 fixed capacity heat pump

Model	IGLU Aleut Max 70
Air-to-water heat pump	No
Water-to-water heat pump	No
Ground-to-water heat pump	Yes
Low temperature heat pump	No
Equipped with supplementary heater	No
Supplementary heater is used	No

Parameters applied using average temperature are declared. Parameters are declared under average climatic conditions.

Parameter	Conventional representation	Value	Measurement unit
Rated thermal power	P_{rated}	70	kW
Declared part load heating capacity at 20 °C indoor temperature and outdoor temperature T_j			
T_j = – 7 °C	P_{dh}	70,04	kW
T_j = + 2 °C	P_{dh}	70,60	kW
T_j = + 7 °C	P_{dh}	71,16	kW
T_j = + 12 °C	P_{dh}	71,78	kW
T_j= (T_{biv})- bivalent temperature mode	P_{dh}	-	kW
T_j = operating limit temperature	P_{dh}	-	kW
Air-to-water heat pump: **T_j** = -15°C (where TOL <-20°C)	P_{dh}	-	kW
Bivalent temperature	T_{biv}	-	°C
Power in cyclic heating mode	P_{cych}	-	kW
Decreased efficiency in cyclic mode	C_{dh}	0,99	—
Power consumption in modes other than active mode			
Off mode	P_{OFF}	0,009	kW
Thermostat-off mode	P_{TO}	0,009	kW
Standby mode	P_{SB}	0,064	kW
Crankcase heater mode	P_{CK}	-	kW
Other parameters			
Capacity control	fixed		
Sound power level, indoors/outdoors	L_{WA}	57/0	dB
Emissions of nitrogen oxides	NO_x	-	mg/kWh
Contact details	IGLU TECH UAB		Ukmerges st. 364-6, Vilnius, Lithuania

Parameter	Conventional representation	Value	Measurement unit
Seasonal energy efficiency for space heating	η_s	135	%
Declared efficiency coefficient or ratio of primary energy to radiant heat output at room temperature 20 °C and outdoor temperature T_j			
T_j = – 7 °C	COP_d arba PER_d	4,59	–
T_j = + 2 °C	COP_d arba PER_d	4,64	–
T_j = + 7 °C	COP_d arba PER_d	4,78	–
T_j = + 12 °C	COP_d arba PER_d	4,97	–
T_j= (T_{biv})- bivalent temperature mode	COP_d arba PER_d	-	–
T_j = operating limit temperature	COP_d arba PER_d	-	°C
Air-to-water heat pump: **T_j** = -15°C (where TOL <-20°C)	COP_d arba PER_d	-	
Air-to-water heat pump: operating limit temperature	TOL	-	°C
Cyclical efficiency	COP_{cyc} or PER_{cyc}	-	– or %
Heating water limit operating temperature	WTOL	60	°C
Supplementary heater			
Rated thermal power	P_{sup}	-	kW
Type of energy input	Electricity		
Air-to-water heat pump: rated air flow rate, outdoor	—		m^3/h
Ground-to-water heat pump: water flow, outdoor heat exchanger		17	m^3/h

Technical data of IGLU Aleut Max 90 fixed capacity heat pump

Model	IGLU Aleut Max 90
Air-to-water heat pump	No
Water-to-water heat pump	No
Ground-to-water heat pump	Yes
Low temperature heat pump	No
Equipped with supplementary heater	No
Supplementary heater is used	No

Parameters applied using average temperature are declared. Parameters are declared under average climatic conditions.

Parameter	Conventional representation	Value	Measurement unit
Rated thermal power	P_{rated}	87	kW
Declared part load heating capacity at 20 °C indoor temperature and outdoor temperature T_j			
T_j = – 7 °C	P_{dh}	87,03	kW
T_j = + 2 °C	P_{dh}	87,35	kW
T_j = + 7 °C	P_{dh}	87,55	kW
T_j = + 12 °C	P_{dh}	87,63	kW
T_j= (T_{biv})- bivalent temperature mode	P_{dh}	-	kW
T_j = operating limit temperature	P_{dh}	-	kW
Air-to-water heat pump: **T_j** = -15°C (where TOL <-20°C)	P_{dh}	-	kW
Bivalent temperature	T_{biv}	-	°C
Power in cyclic heating mode	P_{cych}	-	kW
Decreased efficiency in cyclic mode	C_{dh}	0,99	—
Power consumption in modes other than active mode			
Off mode	P_{OFF}	0,009	kW
Thermostat-off mode	P_{TO}	0,009	kW
Standby mode	P_{SB}	0,064	kW
Crankcase heater mode	P_{CK}	-	kW
Other parameters			
Capacity control	fixed		
Sound power level, indoors/outdoors	L_{WA}	64/0	dB
Emissions of nitrogen oxides	NO_x	-	mg/kWh
Contact details	IGLU TECH UAB		Ukmerges st. 364-6, Vilnius, Lithuania

Parameter	Conventional representation	Value	Measurement unit
Seasonal energy efficiency for space heating	η_s	131	%
Declared efficiency coefficient or ratio of primary energy to radiant heat output at room temperature 20 °C and outdoor temperature T_j			
T_j = – 7 °C	COP_d arba PER_d	4,51	–
T_j = + 2 °C	COP_d arba PER_d	4,62	–
T_j = + 7 °C	COP_d arba PER_d	4,74	–
T_j = + 12 °C	COP_d arba PER_d	4,81	–
T_j= (T_{biv})- bivalent temperature mode	COP_d arba PER_d	-	–
T_j = operating limit temperature	COP_d arba PER_d	-	°C
Air-to-water heat pump: **T_j** = -15°C (where TOL <-20°C)	COP_d arba PER_d	-	
Air-to-water heat pump: operating limit temperature	TOL	-	°C
Cyclical efficiency	COP_{cyc} or PER_{cyc}	-	– or %
Heating water limit operating temperature	WTOL	60	°C
Supplementary heater			
Rated thermal power	P_{sup}	-	kW
Type of energy input	Electricity		
Air-to-water heat pump: rated air flow rate, outdoor	—		m^3/h
Ground-to-water heat pump: water flow, outdoor heat exchanger		23	m^3/h



UAB IGLU TECH

Ukmergės g. 364-6, LT-14188 Vilnius

Tel: +370 655 53277

E-mail: info@iglutech.eu

http://iglutech.eu/en/